



VIPER 13K SERIES

BULLWHEEL UNDERGROUND PULLER

VIPER 13K FEATURES

OVERVIEW

THE ENVOLTZ VIPER 13K UNDERGROUND PULLER IS AN ADVANCED BULLWHEEL PULLING MACHINE WITH TELESCOPING BOOM AND ALL POSITION QUADRANT BLOCK TO QUICKLY GET THE JOB DONE. WITH INNOVATIONS SUCH AS DIRECT DRIVES, PATENTED SPOOLING SYSTEM, ADVANCED CONTROLS, INTUITIVE USER INTERFACE, FAIL-SAFE BRAKING, AND USER FRIENDLY REMOTE CONTROL, ENVOLTZ OFFERS A SAFE, EFFICENT PULLER TO SAVE BOTH TIME AND MONEY.



ADVANCED PULLING

- DUAL HARDENED GROOVED BULLWHEELS
- DIRECT DRIVE PLANETARY/HYDRAULIC MOTOR ASSEMBLY
- NO CHAINS OR UNCESSARY BEARINGS
- INTEGRATED SPRING APPLIED/HYDRAULIC RELEASE BRAKES
- TAKE UP DRUM WITH 3,280 FT STORAGE OF 9/16" ROPE
- LOAD PIN FOR PRECISE TENSION SENSING AND READOUT
- SPEED ENCODER FOR ACCURATE LINESPEED/FOOTAGE
- UTILIZES THE ENVOLTZ SMART SPOOLER





PATENTED SMART SPOOLING

- ENVOLTZ PATENTED SMART SPOOLER LEVELWIND FOR CONTROLLED SPOOLING ONTO THE TAKE UP DRUM
- DUAL SHEAVE ARM MOUNTED ON HYDRAULICALLY DRIVEN HEAVY DUTY SEALED SLEW BEARING
- ARM PIVOT PROGRAMMED TO MATCH TAKE UP DRUM ROTATIONAL SPEED FOR PRECISE SPOOLING
- SMART SPOOLER CAN BE EASILY PROGRAMMED FOR DIFFERENT ROPE DIAMETERS WITH TOUCH OF BUTTON

TELESCOPING BOOM

- HYDRAULICALLY CONTROLLED TELESCOPING BOOM ELIMINATES NEED FOR ADDITIONAL SETUP ROLLERS
- TELESCOPES UP TO 12FT BELOW GRADE
- RATED AT FULL 13K PULLING CAPACITY
- TOP 20" LARGE DIAMETER NYLATRON SHEAVE ALLOWS PULL OF MAKE UP CONDUCTOR
- ENVOLTZ ALL POSITION QUADRANT BLOCK ALLOWS FOR QUICK CABLE ROUTING WITH MULTIPLE TIE BACK POSITIONS





ADVANCED CONTROLS

- CURBSIDE CONSOLE WITH 12" TOUCHSCREEN HMI, PROPORTIONAL JOYSTICKS, ROTARY KEYPAD, AND DATA PORT
- INTUITIVE USER INTERFACE FOR FUNCTION CONTROL, REAL TIME MACHINE STATUS, DIAGNOSTICS, AND SETTINGS
- DATA LOGGING AVAILABLE VIA DATA USB PORT
- E-STOPS AT MAIN CONTROL AND AT CORNERS OF MACHINE
- ALL COMPONENTS RUGGED AND IP67 RATED
- PROGRAMMING IN HOUSE, CUSTOM UI OPTIONS AVAILABLE





FUNCTIONAL ACCESSORIES

- ENVOLTZ GAME CONTROLLER STYLE REMOTE FOR FOR FULL OPERATION, REAL TIME MACHINE STATUS, AND E-STOP
- REMOTE USES READILY AVAILABLE MILWAUKEE M18 BATTERIES (CHARGER AND BATTERIES PROVIDED)
- RADIO TETHER IN CASE OF SIGNAL ISSUES/DEAD BATTERY
- STREET SIDE AND TONGUE WEATHERPROOF TOOLBOXES
- ALL-ANGLE SHEAVE AT REAR (WHEN BOOM NOT NEEDED)
- WORK AND GROUND LIGHTS FOR NIGHTTIME OPERATION



ELECTRIFICATION READY

- VIPER CAN BE POWERED EITHER WITH KUBOTA 49HP FINAL TIER 4 DIESEL ENGINE OR THE 50HP ENVOLTZ E-CELL
- E-CELL OPTION COMBINES AN ADVANCED LITHIUM BATTERY PACK WITH A HIGH TORQUE ELECTRIC MOTOR
- ZERO EMMISION, QUIET OPERATION WITH THE E-CELL
- LEVEL 1 AND 2 J1772 EV CHARGING ON ELECTRIC OPTION
- SAME HYDAULIC PUMP IS USED FOR EITHER POWER UNIT OPTION

CUSTOMIZABLE







VIPER 13K SERIES SPECIFICATIONS

FEATURE

POWER UNIT

ENGINE

ENGINE INTERFACE

FUEL CAPACITY

PULLING CAPACITY

PULLER

BULLWHEELS

BULLWHEEL DRIVES

TAKE UP DRUM

TAKE UP DRUM DRIVE

TAKE UP STORAGE

LEVELWIND

LOAD SENSING

FOOTAGE COUNTER

BOOM

QUADRANT BLOCK

ALL ANGLE SHEAVE

MAIN CONTROLS

REMOTE CONTROL

MANUAL CONTROLS

STABILIZING JACKS

FRAME CONSTRUCTION

SUSPENSION

TIRE & WHEELS

TRAILER BRAKES

LIGHTING SYSTEM

HITCH

HYDRUALIC FLUID

ACCESSORIES

DIMENSIONS

TOOL CIRCUIT (OPTION)

DIESEL

DIESEL OVER HYDRAULIC

49HP FINAL TIER 4 DIESEL WATERCOOLED/ELECTRIC START 4.3" HD IP67 COLOR OPERATOR CONTROL SCREEN

15 GALLONS

ELECTRIC

BATTERY OVER HYDRAULIC

50HP ENVOLTZ E-CELL ELECTRIC ENGINE 4.3" HD IP67 COLOR OPERATOR CONTROL SCREEN

33 kWh LiFePO PACK

13,000 LBS @ 60 FPM / 6,500 LBS @ 120 FPM

DUAL BULLWHEEL DIRECT DRIVE PULLER INTEGRATED TAKE UP DRUM WITH ENVOLTZ SMART SPOOLER

PRECISION MACHINED, 5 HARDENED GROOVES

INDEPENDENT DIRECT DRIVE HYDRAULIC MOTORS/GEARBOXES INTEGRAL SPRING APPLIED / HYDRAULIC RELEASE FAIL SAFE BRAKE LARGE DIAMETER MACHINED STORAGE DRUM SUPPORTED BY HEAVY DUTY PILOTED FLANGE BEARINGS INDEPENDENT DIRECT DRIVE HYDRAULIC MOTOR/GEARBOX INTEGRAL SPRING APPLIED / HYDRAULIC RELEASE FAIL SAFE BRAKE

3,280 FT OF 9/16" BRAIDED STEEL ROPE

ENVOLTZ PATENTED SMART SPOOLER

LOAD PIN FOR PRECISE TENSION MEASUREMENT

ENCODER FOR ACCURATE SPEED AND FOOTAGE

HYDRAULIC CONTROLLED TELESCOPING BOOM

RATED AT MAX PULL AT 12FT BELOW GRADE
ALL POSITION ENVOLTZ QUADRANT BLOCK, LARGE DIAMETER NYLATRON ROLLERS
TIE BACK READY, 36" OVERALL BENDING RADIUS
SLEW BEARING MOUNTED ALL ANGLE SHEAVE, FULL 360 DEGREE ROTATION

SLEW BEARING MOUNTED ALL ANGLE SHEAVE, FULL 360 DEGREE ROTATION
FOR PULLS WHERE BOOM NOT NEEDED
CURBSIDE OPERATOR CONSOLE WITH 12" TOUCHSCREEN DISPLAY
INTUITIVE UI FOR CONTROL AND DIAGNOSTICS, PROPTIONAL CONTROL JOYSTICKS
GAME CONTROLLER STYLE WITH 4.3" DISPLAY, (2) THUMB CONTROL JOYSTICKS,
SELECTOR PUSH BUTTONS, MILWAUKEE M18 BATTERY, 30FT MIN LINE OF SIGHT, TETHER
CURBSIDE MANUAL CONTROL CONSOLE WITH REMOVABLE LEVERS
PROPORTIONAL CONTROL OF MAJOR FUNCTIONS FOR BACK UP CONTROL OPTION
(3) 12,000 LBS HYDRAULIC STABILIZER JACKS
CONTROLLED FROM MAIN CONSOLE, REMOTE, MANUAL CONSOLE, OR LOCAL CONTROL

FULLY WELDED BOXED IN CONSTRUCTION

TANDEM INDEPENDENT AXLELESS

ST235/80R15 TIRES ON SINGLE PIECE CONSTRUCTION RIMS

ELECTRIC W/BREAKAWAY

FMVSS 10 AND US DOT LED, 12VDC, PUDDLE LIGHTS FOR GROUND ILLUMINATION, WORK LIGHT'S AND REAR FLOOD LIGHTS (OPTIONAL)
3" WALLACE FORGE LUNETTE EYE WITH ADJUSTABLE COUPLER

PINTLE EXTENSION (OPTIONAL)

AW46, 30 GALLON TANK CAPACITY

48" TOOLBOXES W/T-HANDLE LATCHES AND LOCKS 12V MILWAUKEE BATTERY CHARGER, WORDEN WHEEL CHOCKS WITH STORAGE

204" L x 96" W x 125" H @ 10,400 LBS

QUICK DISCONNECT 2,500 PSI @ 13 GPM MAX

